



Series Stainless Steel

RTX-SS

N

1450rpm

Ø 30mm

P	Code	Description	Q	Assembly prescription	Validity	P	Code	Description	Q	Assembly prescription	Validity
1	4049201	Head assembly	Ø 36	1		79	1941290	Ring	1		
2	4040210	Head		1		80	1941260	Plate	1		
7	4040120	Plug	1/4" G s.steel	1	C=15Nm	81	1941270	Level gauge	1		
8	820511	O-ring	Ø 10,82x1,78 Viton	1		82	100410	O-ring	Ø 34,6x2,62	1	
9	4040060	Plug	stainless steel	6		83	3660260	Shim 0.05mm	1		
10	2821390	Ring	anti-extrusion	6		83	3660270	Shim 0.10mm	1		
11	4049051	Complete valve	delivery	6		83	3660280	Shim 0.19mm	1		
12	1540631	O-ring	Ø 23,47x2,62 Viton	3		84	180031	Screw	TCEI M8x20	12	
13	4049050	Complete valve	suction	3		85	3660060	Shaft	3 marked	1	
20	3660510	Ring	support Ø 36	3	Lubricate with grease Molykote PG54	86	3660320	Key		1	
21	3661260	Water seal	Ø 36	3		88	4040040	Cover		1	
22	3660520	Ring	anti-extrusion	3	Lubricate with grease Molykote PG54	89	3660300	Ring	seal	1	
23	4040160	Piston guide	front Ø 36	3		A	43520	Valve kit		1	
24	3660730	Gasket		3		B	42839	Piston kit	Ø 36	1	
25	3660550	Ring	anti-extrusion	3		C	42840	Oil seal kit		1	
26	4040150	Piston guide	rear Ø 36	3		E	43519	Water seal kit	Ø 36	1	
27	1320361	O-ring	Ø 47,35x1,78 Viton	3		H	43765	Piston guide kit	Ø 36	1	
28	3660310	Ring	seal	3							
40	4040010	Pump body		1							
41	850261	Screw	TCEI M10x90	8							
43	3660350	Oil plug	with oil dipstick	1							
46	3660360	O-ring	Ø 183,82x2,62	1							
47	680700	Screw	TCEI M6x20	8							
50	4040070	Screw		3							
51	3660342	O-ring	Ø 12x2 Viton	3							
52	3660130	Piston	Ø 36	3							
53	4040170	Plate		3							
55	3660081	Piston	guide	3							
56	3660330	Ring		6							
57	3660090	Pin		3							
58	3660070	Connecting-rod	aluminium	3	C=22Nm / Loxeal 55-14						
65	4040030	Cover		1							
70	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54						
71	2282280	Plug	with magnet	1	C=20Nm						
75	3660290	Bearing		2							
76	3660740	O-ring	Ø 83x3	2							
77	4049000	Cover	complete	1							
78	4040050	Cover		1							

Revision: 1

Oil type: SAE 75W90

Validity: < XX/YY = From week/year

Date: 31/05/2024

Oil quantity: 2,000 Kg

C= Tightening torque (Tolerance +0 ÷ -10%)

* = Not present for electric pump